


Raw 30 PVC Black
INFAB Bfab/3 EM 12-00+00 (V) AS BK 2.8mm
01010085

GENERAL CHARACTERISTICS

3 ply PVC bare by bare black. Antistatic.

BEST USED FOR

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.11in	2.8mm
Mass	0.62lb/ft ²	3kg/m ²
Tensile force at 1% elongation	68lbf/in	12N/mm
	After Relaxation - ref. ISO 21181	
Working Temp.	+14/+176F°	-10/+80C°
Flexion (A)	3.15in 80mm	
Counter Flexion (B)	3.15in 80mm	
Coefficient of friction (bottom side) - Steel	0.25	

TENSION MEMBER

Interply	PVC
Fabric	Polyester Rigid (EM)
Plies	3
Weft	Rigid (R)

TOP SIDE (CARRYING)

Material	Fabric
Color	Black (B)
Thickness	0in 0mm
Hardness	-
Surface	Impregnated (00)

BOTTOM SIDE (PULLEY)

Material	Fabric
Color	White (W)
Thickness	0in 0mm
Hardness	-
Surface	Impregnated (00)

SPECIAL CHARACTERISTICS

- ✓ **Antistatic**
ISO 284 & 21178
- ✓ **Hydrolysis Resistant**

Raw 30 PVC Black
INFAB Bfab/3 EM 12-00+00 (V) AS BK 2.8mm
01010085

SPLICE INSTRUCTIONS (PREFERRED)



STEP SPLICE


Temperature:
Pressure:
**WATER
COOL**
**180 C°
356 F°**
**29 PSI
2 Bars**
**AIR
COOL**
**180 C°
356 F°**
**7.3 PSI
0.5 Bars**

- Release Paper
- Belt (Conveying Side Up)
- Foil (Between Plies)
- Release Paper


Temperature:
Pressure:
**180 C°
356 F°**
**29 PSI
2 Bars**
**180 C°
356 F°**
**7.3 PSI
0.5 Bars**
Dwell Time:
0.00 Min
2.00 Min
Note: Foil is optional for air cooled.

MECHANICAL JOINING METHOD (at smallest pulley diameter)


Recessed Lacing
NO

Hidden Lacing
NO



Staple Lacing
RS62

Plastic Spiral Lacing
YES




Spiral Finger
NO


APF Fasteners
APF-150

Alligator
7

Clipper Lacing
25 LP, 30P, UX-1 SP, UCM36, 36, 1 SP, UX-1 LLSP, 1 LLSP, 30LP, 36 LL, 36 LLLP, UCM36 LL

**Slider
Bed**

**Flat
Rollers**

**Slider Beds
on Both Sides**

**Channel
Trough**

**Conventional
Trough**

**Incline
Conveying**

**Incline
Variation**

**Bucket
Elevator**

**Conveyor with
Accumulation**

**Bend
Conveyor**

**Knife Edge
Conveyor**


● Applicable ● Limited Use ● Not Applicable

WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer or birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov

*Because of continuous development above data is subjected to change without prior notice by INO USA. This data replaces that included in previous publications. INO USA excludes any liability for the incorrect use of the above stated information.

RELEASED 01/04/2021