


Raw 10 PVC
INFAB BV/2 EM8 - 0+0 PVC trans F AS
11027

GENERAL CHARACTERISTICS

2 ply PVC, bare x bare. Antistatic. Food approved.
Oil and fat resistant

BEST USED FOR

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.06in	1.6mm
Mass	0.37lb/ft ²	1.8kg/m ²
Tensile force at 1% elongation	46lbf/in	8N/mm
Working Temp.	+14/+176F°	-10/+80C°
Flexion (A)	1.57in 40mm	
Counter Flexion (B)	1.57in 40mm	
Coefficient of friction (bottom side) - Steel	0.20	

TENSION MEMBER

Interply	PU
Fabric	Polyester Rigid (EM)
Plies	2
Weft	Rigid (R)

TOP SIDE (CARRYING)

Material	Fabric
Color	Fabric (FA)
Thickness	0in 0mm
Hardness	-
Surface	Bare (0)

BOTTOM SIDE (PULLEY)

Material	Fabric
Color	Fabric (FA)
Thickness	0in 0mm
Hardness	-
Surface	Bare (0)

SPECIAL CHARACTERISTICS

- ✓ **Food Approved, FDA compliance**
acc.to 21 CFR parts 170-19
- ✓ **Food Approved, EU compliance**
(EC) No. 1935/2004 & (EU) No. 10/2011


- ✓ **Antistatic**
ISO 284 & 21178
- ✓ **Hydrolysis Resistant**

- ✓ **Oil & Fat Resistant**



Raw 10 PVC
INFAB BV/2 EM8 - 0+0 PVC transp F AS
11027

SPLICE INSTRUCTIONS (PREFERRED)



STRAIGHT FINGERS (SF)


Temperature:
Pressure:
**WATER
COOL**
**AIR
COOL**
**170 C°
338 F°**
**170 C°
338 F°**
**29 PSI
2 Bars**
**7.3 PSI
0.5 Bars**
 **Release Paper**
 **Foil**
 **Belt (Conveying Side Up)**
 **Release Paper**

Temperature:
Pressure:
**170 C°
338 F°**
**170 C°
338 F°**
**29 PSI
2 Bars**
**7.3 PSI
0.5 Bars**
Dwell Time:
0.00 Min
0.00 Min
Note: Foil is optional for air cooled.

MECHANICAL JOINING METHOD (at smallest pulley diameter)


Recessed Lacing
NO

Hidden Lacing
NO




Staple Lacing -

Plastic Spiral Lacing
YES



Spiral Finger
YES

APF Fasteners APF-100

Alligator
00, 1

Clipper Lacing
25, UCM36 SLXSP, UCM36 SLSP, 25 LP, UCM36 XSP, UCM36 SP, UX-1 SP, UX-1 LLSP

**Slider
Bed**

**Flat
Rollers**

**Slider Beds
on Both Sides**

**Channel
Trough**

**Conventional
Trough**

**Incline
Conveying**

**Incline
Variation**

**Bucket
Elevator**

**Conveyor with
Accumulation**

**Bend
Conveyor**

**Knife Edge
Conveyor**


● Applicable ● Limited Use ● Not Applicable

WARNING: This product can expose you to chemicals including DINP, which is known to the State of California to cause cancer or birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov

*Because of continuous development above data is subjected to change without prior notice by INO USA. This data replaces that included in previous publications. INO USA excludes any liability for the incorrect use of the above stated information.

RELEASED 01/04/2021